

GOLDENSTONE® 2T MIX

Technical Data Sheet (TDS) TWO-CYCLE GASOLINE ENGINE OILS

Description and Application

Goldenstone® 2T Mix is low-ash mineral oil intended for “premix” lubrication of conventional two-cycle, air-cooled gasoline engines in passenger cars, motorcycles, motorbikes, mopeds, motocultivators, chainsaws etc. The recommended Oil -to-Fuel Ratio is 1:50 (or other ratio recommended by the equipment manufacturer).

Benefits

- Good lubricating properties
- Good detergent properties
- Low power losses at start-up
- A low smoke tendency
- Provides for clean and in good condition exhaust port

Specifications

	Goldenstone® 2T Mix
ISO	L-EGB
JASO	FC
API	TC

Typical Characteristics

Parameter	Test Method	Typical Value
Density at 20°C, g/ml	EN ISO 3675	0.880
Kinematic Viscosity at 40°C, mm ² /s	EN ISO 3104	78
Flash point COC, °C	EN ISO 2592	200
Pour point, °C	ISO 3016	-15
TBN (HClO ₄), mg KOH/g	ASTM D 2896	1.0

Important note: typical data values do not constitute a specification but are an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved.

Health, Safety and Handling

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application.

For more information about product MSDS, terms and conditions for storage and shelf life please visit:

www.goldenstoneoils.com

Packages

1L, 210L, 1000L