

GOLDENSTONE® MULTIGAS SAE 10W-40

Technical Data Sheet (TDS) PASSENGER CAR ENGINE OILS

Description and Application

Goldenstone® Multigas 10W-40 is semi-synthetic multigrade engine oil, formulated with a special selection of high quality solvent refined and hydrotreated base stocks and a special advanced additive technology system.

Goldenstone® Multigas 10W-40 is recommended for application in passenger car engines converted to burn liquefied natural gasses (methane). This product is especially engineered for engines burning both gasoline and LNG.

Benefits

- Excellent protection against engine wear
- Cleanliness in combustion area
- Extended spark plug life
- Excellent oxidation and nitration protection
- Extended engine durability, respectively life

Specifications

	SAE 10W-40
ACEA	A3/B3
API	SL
MB	229.1
VW	501 01

Typical Characteristics

Parameter	Test Method	Typical Value
Density at 20°C, g/ml	EN ISO 3675	0.864
Kinematic Viscosity at 100°C, mm ² /s	EN ISO 3104	14.6
Kinematic Viscosity at 40°C, mm ² /s	EN ISO 3104	98
Viscosity Index	ISO 2909	155
Flash point COC, °C	EN ISO 2592	222
Pour point, °C	ISO 3016	-33
TBN (HClO ₄), mg KOH/g	ASTM D 2896	8.9
Sulfated Ash, %	EN ISO 3987	0.95

Important note: typical data values do not constitute a specification but are an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved.

Health, Safety and Handling

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application.

For more information about product MSDS, terms and conditions for storage and shelf life please visit:

www.goldenstoneoils.com

Packages

20L, 210L