

GOLDENSTONE® ULTRA G2 SAE 5W-30

Technical Data Sheet (TDS)

HIGH PERFORMANCE PASSENGER CAR ENGINE OILS

Description and Application

Goldenstone® Ultra G2 5W-30 multigrade engine oil is fully synthetic product blended according to the latest advanced low SAPS lubricant technology and designated for lubrication of today's engines in passenger cars, light trucks and vans. **Goldenstone® Ultra G2 5W-30** is latest generation synthetic multigrade engine oil with extended oil drain interval. It is designated for use in the most modern heavily loaded diesel and gasoline engines of passenger cars and light-duty vehicles equipped with diesel particulate filters (DPF) and aftertreatment devices (TWC). It is particularly suitable for GM cars demanding dexos2™ and engines where GM-LL-B-025 and GM-LL-A-025 oils are recommended as dexos2™ supersedes GM-LL-B-025 and GM-LL-A-025.

Benefits

- protects diesel engines from harmful soot deposits
- designed with limits on certain chemical components to prolong catalyst life and protect expensive emission reduction systems
- robust oil, resisting degradation between oil changes and maintaining optimum performance longer

Specifications

	SAE 5W-30
GM	dexos 2 License No.: RB2F0218077
ACEA	C3
API	SN/CF
MB	229.31

Typical Characteristics

Parameter	Test Method	Typical Value
Density at 20°C, g/ml	EN ISO 3675	0.852
Kinematic Viscosity at 100°C, mm ² /s	EN ISO 3104	12.3
Kinematic Viscosity at 40°C, mm ² /s	EN ISO 3104	75
Viscosity Index	ISO 2909	162
Flash point COC, °C	EN ISO 2592	230
Pour point, °C	ISO 3016	-39
TBN (HClO ₄), mg KOH/g	ASTM D 2896	7.7
Sulfated Ash, %	EN ISO 3987	0.8

Important note: typical data values do not constitute a specification but are an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved.

Health, Safety and Handling

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application.

For more information about product MSDS, terms and conditions for storage and shelf life please visit:

www.goldenstoneoils.com

Packages

1L, 4L, 20L, 210L, 1000L