

GOLDENSTONE® ULTRA V SAE 5W-30

Technical Data Sheet (TDS)

HIGH PERFORMANCE PASSENGER CAR ENGINE OILS

Description and Application

Goldenstone® Ultra V 5W-30 is synthetic multigrade engine oil especially designed for the lubrication of Volkswagen, AUDI, SEAT and Skoda engines. It is formulated from high quality synthetic base components with the addition of a unique additive system to obtain a lubricant which is fully compatible with exhaust gas after treatment devices, exhibits high temperature stability, wear protection, excellent low-temperature performance and reduced hazardous emissions in the exhaust gasses.

Goldenstone® Ultra V 5W-30 is a special product, especially developed for use in Volkswagen, AUDI, SEAT and Skoda gasoline and diesel engines with extended oil drain intervals. It is fully compatible with diesel particulate filters (DPF) and the additional exhaust gas aftertreatment devices and is suitable for the advanced FSI and TSI gasoline engines with direct fuel injection.

Benefits

- Cleanliness of all engine parts
- Fuel consumption reduction
- Maximum protection against wear and corrosion
- Extends life and maintains the effectiveness of DPFs
- Environmental friendliness (aids to reduce hazardous impact on environment)
- A special friction modifier ensuring maximum wear protection

Specifications

	SAE 5W-30
VW	504 00/507 00
ACEA	C3
API	SN
BMW	Long Life 04
MB	229.51
Porsche	C30

Typical Characteristics

Parameter	Test Method	Typical Value
Density at 20°C, g/ml	EN ISO 3675	0.850
Kinematic Viscosity at 100°C, mm ² /s	EN ISO 3104	11.8
Kinematic Viscosity at 40°C, mm ² /s	EN ISO 3104	66.8
Viscosity Index	ISO 2909	174
Flash point COC, °C	EN ISO 2592	234
Pour point, °C	ISO 3016	-45
TBN (HClO ₄), mg KOH/g	ASTM D 2896	8.7
Sulfated Ash, %	EN ISO 3987	0.8

Important note: typical data values do not constitute a specification but are an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved.

Health, Safety and Handling

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application.

For more information about product MSDS, terms and conditions for storage and shelf life please visit:

www.goldenstoneoils.com

Packages

1L, 4L, 20L, 210L, 1000L