

Goldenstone® Compressor Synth

Technical Data Sheet (TDS) Compressor Oils

Description and Application

GOLDENSTONE® Compressor Synth lubricants are formulated with advanced PAO synthetic technology and latest generation additive systems designed to provide exceptional system performance and complete protection.

GOLDENSTONE® Compressor Synth is recommended for lubrication of all types of compressors, including single and multistage reciprocating units and single or multistage centrifugal compressors, and is particularly recommended for use in rotary screw units of various OEM's inc. Atlas Copco, ABB and Tanabe

The high performance thermal stability allows GOLDENSTONE® Compressor Synth to protect oil-injected rotary screw compressors with high discharge temperatures of +100°C at 15 bar and extending drain intervals.

GOLDENSTONE® Compressor Synth oils are recommended for use in marine diesel turbochargers where two separate lubrication systems are in use.

Benefits

- excellent turbocharger protection
- long service performance
- exceptional wear performance
- high stable oxidation resistance
- drain interval up to 5000 hours

Specifications

| ISO 6743/6 | ISO- L-DAB, ISO-L-DAJ |
|------------|-----------------------|
| ISO 3448 | VG 46, 68 |
| DIN 51506 | VDL |

Typical Characteristics

| Parameter | Test Method | Typical Value | |
|--|--------------|---------------|-------|
| | | 46 | 68 |
| Density at 20°C, g/ml | EN ISO 3675 | 0.842 | 0.846 |
| Kinematic viscosity at 40°C, mm ² /s | EN ISO 3104 | 46 | 68 |
| Kinematic viscosity at 100°C, mm ² /s | EN ISO 3104 | 8.1 | 10.3 |
| Viscosity Index | ISO 2909 | 136 | 141 |
| Flash point, COC, °C | EN ISO 2592 | 240 | 250 |
| Pour point,°C | ISO 3016 | -57 | -57 |
| Rust Preventive Properties in the presence of | ISO 7120 A/B | | |
| distilled and synthetic water | | Pass | |
| FGZ, Fail load stage | DIN 51324 | 12 | 12 |

Important note: Typical data values do not constitute a specification but are an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved.

Health, Safety and Handling

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application.

For more information about product MSDS, terms and conditions for storage and shelf life please visit: www.goldenstoneoils.com

Packages

210L, Bulk

Version: March 14, 2018