

Goldenstone® KM

Technical Data Sheet (TDS) Mould release oils

Description and Application

GOLDENSTONE® KM mould release oils are formulated from selected highly refined paraffinic-naphthenic base oils blended with an additive package, imparting very good lubricating, adhesion and mould release properties to the oils as well as ensuring dependable corrosion protection of formworks and easy separation during removal of shutters (deshuttering).

GOLDENSTONE® KM oils are developed for the lubrication of formworks (shutters) in the production of concrete, reinforced concrete and aerated concrete products and components as they facilitate their removal from the formworks during deshuttering. They can be applied by brush or sprayer (**GOLDENSTONE® KM-10 & 15**). When the proper viscosity grade oil has been chosen the oil consumption can be reduced to less than 1 liter per 20-25 m² area of formworks/shutters.

Benefits

- Easy deshuttering
- Preserving the form of the elements
- Corrosion prevention
- Ensures cleanliness of the formworks

Specifications

ISO 3448	VG 10, VG 15

Typical Characteristics

Parameter	Test Method	Typical Value	
		VG 10	VG 15
Density at 20°C, g/ml	EN ISO 3675	0.867	0.873
Kinematic Viscosity at 40°C, mm ² /s	EN ISO 3104	10	15
Kinematic Viscosity at 20°C, mm ² /s	EN ISO 3104	22.1	35.1
Flash point COC, °C	EN ISO 2592	165	175
Pour point, °C	ISO 3016	-12	-12
Saponification Number, mgKOH/g	BDS 5496	4.0	4.0
Steel corrosion 50°C	BDS 5747	pass	

Important note: typical data values do not constitute a specification but are an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved.

Health, Safety and Handling

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application.

For more information about product MSDS, terms and conditions for storage and shelf life please visit:

<http://www.goldenstoneoils.com>

Packages

210l, 1000l, Bulk