

GOLDENSTONE® SUPER SAE 15W-50

Technical Data Sheet (TDS) MULTIGRADE ENGINE OILS

Description and Application

Goldenstone® Super 15W-50 multigrade engine oil is formulated with a special selection of high quality solvent refined and hydrotreated base stocks and a performance additive package to ensure conformance with the requirements of API CF/CD/SF performance levels.

Goldenstone® Super 15W-50 multigrade engine oil is intended for application in older models of heavy-loaded, naturally aspirated or turbocharged diesel engines operating at variable conditions and a wide temperature range in commercial trucks, buses, farm and construction equipment and machines.

It can also be used in gasoline engines whose manufacturers prescribe the application of API SF performance level lubricants.

Benefits

- Engine cleanliness
- Thermal and oxidation stability
- Stable lubricating film

Specifications

	SAE 15W-50
API	CF/CD/SF

Typical Characteristics

Parameter	Test Method	Typical Value
Density at 20°C, g/ml	EN ISO 3675	0.886
Kinematic Viscosity at 100°C, mm ² /s	EN ISO 3104	18.6
Kinematic Viscosity at 40°C, mm ² /s	EN ISO 3104	145.1
Viscosity Index	ISO 2909	145
Flash point COC, °C	EN ISO 2592	228
Pour point, °C	ISO 3016	-28
TBN (HClO ₄), mg KOH/g	ASTM D2896	9.0
Sulfated Ash, %	EN ISO 3987	1.25

Important note: typical data values do not constitute a specification but are an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved.

Health, Safety and Handling

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application.

For more information about product MSDS, terms and conditions for storage and shelf life please visit:

www.goldenstoneoils.com

Packages

20L, 210L, 1000L