

Goldenstone® MVR

Technical Data Sheet (TDS)

Chainsaw lubricant

Description and Application

GOLDENSTONE® MVR chainsaw chain oil is designated for the lubrication of the chains of chainsaws. Additive package imparting very good adhesion to the cutting tool providing reduced tool wear and lower oil consumption.

GOLDENSTONE® MVR is formulated from highly refined base stocks and special antiwear, anticorrosion additives and tackiness agent.

Product is NOT suitable to lubricate the engine of the chainsaw!

Benefits

- tackiness additive ensures a strong adhesive film to resist 'fling off'
- lower oil consumption
- anti-wear additives increase chain life
- excellent corrosion protection
- can be used in sub zero temperatures

Specifications

ISO 3448	VG 100
ISO 6743/1	ISO-L-AB

Typical Characteristics

Parameter	Test Method	Typical Value
Appearance	Visual	Clear and bright, without mechanical impurities
Color	ISO 2049	5
Kinematic viscosity at 40°C, mm ² / s	EN ISO 3104	110
Viscosity Index	ISO 2909	80
Flash point, COC, °C	ISO 2592	250
Pour point, °C	ISO 3016	-20
Density at 20°C, g/cm ³	EN ISO 3675	0.886

Important note: Typical data values do not constitute a specification but are an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved.

Health, Safety and Handling

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application.

For more information about product MSDS, terms and conditions for storage and shelf life please visit:

www.goldenstoneoils.com

Packages

210L, Bulk